

# AQUA MIX® SEALER'S CHOICE® GOLD RAPID CURE FORMULA

**1. Product Name**

Aqua Mix® Sealer's Choice® Gold Rapid Cure Formula

**2. Manufacturer**

Custom Building Products  
13001 Seal Beach Blvd.  
Seal Beach, CA 90740-2757  
Customer Support: 800-272-8786  
Technical Services: 800-282-8786  
Fax: 800- 200-7765  
Email: [contactus@cbpmail.net](mailto:contactus@cbpmail.net)  
[custombuildingproducts.com](http://custombuildingproducts.com)



**3. Product Description**

Aqua Mix Sealer's Choice® Gold Rapid Cure Formula is a premium, no-sheen, natural-look, Low VOC, water-based, penetrating sealer formulated to provide maximum stain protection, especially in food preparation and serving areas. May also be used as a pre-grouting sealer.

This product complies with EPA and CARB VOC requirements.

**KEY FEATURES**

- May be used as a pre-grouting sealer
- Allows moisture vapor transmission
- The NEW Rapid Cure Formula protects in less than 4 hours
- Designed to achieve optimal penetration into dense, low-porosity surfaces

**AREAS OF USE**

- All porous tile and natural stone (such as marble, granite, slate, travertine and limestone), porcelain, quarry, Saltillo, terra cotta, cement pavers, masonry surfaces, and other porous tile and grout where a natural look is desired
- Effective for interior and exterior applications

**LIMITATIONS**

- Do not allow sealer to come in contact with any non-recommended surface
- May slightly lighten or darken some surfaces
- Sealer will not prevent surface wear or etching from acids or caustic chemicals

**EXPECTED WEAR UP TO 15 YEARS**

- Will vary depending on hardness and texture of surface, type of area, surface wear, frequency, and type of maintenance products used
- Weather conditions, harsh cleaning methods, and high-alkaline, acidic, or solvent-based cleaners will affect wear

**4. Technical Data**

TEST METHOD	TEST RESULTS
Stain Resistance (CTI 72)	Excellent
Service Time	4 hours

**5. Installation**

**METHODS**

**Application**

Read entire label before using. For new installations, sealer can be applied as soon as 48 hours after grouting. Surface must be clean, dry, and free of existing sealers or coatings. Apply using a sponge, brush, paint pad, cotton towel, or sprayer. NOTE: Be sure any sealer that does not penetrate surface is removed from surface within 5 minutes of each application using absorbent paper or cotton towels. If 2 or more coats are applied, allow a minimum of 30 minutes drying time between coats. 2 hours after final coat conduct a test to determine if surface is completely sealed by applying water droplets to the surface. If water is absorbed, apply an additional coat. Wait 2 hours and repeat the test. Ready for surface traffic in 2 hours after final coat. Keep area dry for 12 hours. Achieves a full cure in 24 hours. Clean applicator tools with water after each use.

**Pre-Grouting Application**

Apply over clean stone or tile a minimum of 2 hours prior to grouting - follow application procedures above.

**Coverage**

Approximately 300 to 1,500 sq. ft. (30 m<sup>2</sup> to 139 m<sup>2</sup>) per coat per gallon (3.8 L), depending on type of stone or tile, porosity and texture of surface, temperature, humidity, and method of application.



Handling And Storage

- Close container tightly after each use
- Store in original container only
- Store and use between temperatures of 40° F and 90° F (4° C and 32° C)

CAUTION

MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE EYES AND SKIN. Wear skin and eye protection. Contains glycol ether monobutyl ether. If in eyes, flush with water for at least 15 minutes. If on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention. DO NOT SPRAY.

6. Availability & Cost

Contact the manufacturer or visit [custombuildingproducts.com](http://custombuildingproducts.com) for information about product cost and availability.

	ITEM CODE	SIZE	PACKAGE
USA	030881	1 pt (473 ml)	Bottle
USA	030882-4	1 qt (946 ml)	Bottle
USA	030883	1 gallon (3.8 L)	Bottle
USA	030884	5 gallon (19 L)	Pail
Canada	C030881	1 pt (473 ml)	Bottle
Canada	C030882-4	1 qt (946 ml)	Bottle
Canada	C030883	1 gallon (3.8 L)	Bottle
Canada	C030884	5 gallon (19 L)	Pail

7. Limited Product Warranty

Custom Building Products warrants to the original consumer purchaser that its product shall be free from defects in material and workmanship under normal and proper usage for a period of one year following the date of original purchase. Custom’s sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom’s printed instructions. Custom makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another.

For details and complete warranty information, visit [custombuildingproducts.com](http://custombuildingproducts.com)

8. Maintenance

Aqua Mix Concentrated Stone & Tile Cleaner or AquaKleen™ or AquaShield™ is recommended for routine spray and wipe cleaning and resealing.

9. Technical Services

For technical assistance contact Custom Building Products or visit [custombuildingproducts.com](http://custombuildingproducts.com).

10. Filing Systems

Additional product information is available from the manufacturer upon request.

Related Products:

- Aqua Mix®
- AquaShield™ Cleaner & Resealer
- AquaKleen™

